

Brighto All Wood Coat

Brighto All Wood Coat matt varnish is an air-drying alkyd based varnish for wooden surfaces. It gives beautiful matt finish without hiding the wood grains. It is used on soft wood, hard wood, plywood, furniture, timberwork such as doors, windows, tables, cupboards etc.. Brighto All Wood Coat gloss varnish can also be applied without any color, if required. It protects the wood two times longer than conventional wood coatings. It gives surface slip effects. Brighto All Wood Coat matt varnish is lead and mercury free.

PACK SIZE: 0.91 L 3.64 L

COLOR RANGE:

Available in clear varnish and for shades, see Brighto All Wood Coat gloss varnish shade card

FILM PROPERTIES:

Chemical Resistance: Resistant to mild chemical attack

Water Resistance: Resistant to levels of atmospheric humidity present in normal environment

COMPOSITION (nominal):

Pigment: N/A

Binder: Alkyd

Solvent: Mineral turpentine.

VOLUME SOLIDS: 45 ± 2% (nominal), other colors will vary

FILM THICKNESS/COAT

Wet: 50 - 75 Micrometers

Dry : 22 - 33 Micrometers

DRYING TIME:

Depends on temperature, humidity, air movements and film thickness

Touch Dry: 2-4 Hours

Recoat: 4-8 Hours

THEORETICAL COVERAGE:A guide to the theoretical coverage which can be achieved under normal conditions is 13.5 - 20m² /litre /coat.

APPLICATION: Brush Roller Spray Sponge

THINNING

Brush or Roller: 10 - 20%

Conventional spray: 30 - 40%

CLEANING UP:

Clean all equipment with mineral turpentine immediately after use.

SURFACE PREPARATION:

Before application, the surface should be clean, dry, free from oil, grease, dust and wax etc. Rub down the surfaces with the help of abrasive paper. Clean with the help of clean cloth. Apply 1-2 coats of Brighto Wood Sealer. Allow it to dry. Slightly rub down the surfaces with the help of abrasive paper after each coat. Clean with the help of clean cloth. Apply 2-3 coats of Brighto All Wood Coat varnish. Stir the varnish thoroughly before use.

FLASH POINT: 33°C

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION

Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contacts with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use turpentine oil or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO₂ fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose of paint waste in accordance with appropriate environmental quality requirements.

Any advice recommendations, information, assistance or service provided by Brighto Paints Pvt. Ltd. in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.