

## Brighto All Wood Lacquer (Matt & Gloss)

Brighto All Wood Lacquer (Matt & Gloss) is a high quality, fast drying, clear topcoat nitrocellulose based lacquer for wooden surfaces. It gives beautiful Matt & Gloss finish without hiding the wood grains. It is used on soft wood, hard wood, plywood, furniture, timberwork such as doors, windows, tables, cupboards etc. . It gives slip effects on the surface applied.

**PACK SIZE:** 0.91 L 3.64 L

**COLOR RANGE:** Clear

### **COMPOSITION (nominal):**

Pigment: N/A

Binder: Nitrocellulose, SO Alkyd

Solvent: Volatile solvents BA, IPA, XYLENE

**VOLUME SOLIDS:** 32 ± 2% (nominal)

### **FILM THICKNESS/COAT:**

Wet: 50 - 75 Micrometers

Dry : 17 - 25 Micrometers

### **DRYING TIME:**

Depends on temperature, humidity, air movements and film thickness

Touch Dry: 15 - 20 Minutes

Recoat: 1- 1 1/2 Hours

### **THEORETICAL COVERAGE:**

A guide to the theoretical coverage which can be achieved under normal conditions is 11-13 m<sup>2</sup> /litre /coat.

**APPLICATION:** Spray

**THINNING:**

Conventional spray: 100 - 150% with Brighto NC Thinner

**CLEANING UP:**

Clean all equipment with Brighto NC Thinner immediately after use.

**SURFACE PREPARATION:**

Before application, the surface should be clean dry and free from oil, grease, dust, wax etc. Rub down the surfaces with the help of abrasive paper. Clean with the help of clean cloth. Apply 1-2 coats of Brighto All Wood Sealer. Allow it to dry. Slightly rub down the surfaces with the help of abrasive paper after each coat. Clean with the help of clean cloth. Apply 2-3 coats of Brighto All Wood Lacquer Matt & Gloss. Stir the product thoroughly before use..

**FLASH POINT:** Matt: 16°C / Gloss: 15.5°C

**SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION:**

Highly inflammable. Keep container tightly closed, up right and out of reach of children. Keep away from the source of ignition e.g. cigarette, matchbox, lighter etc. Protect from extreme of temperature and store in a cool and dry place. Keep away from food, drink and animal feeding stuff. Keep container tightly closed. Wear suitable gloves, mask and safety goggles during application. Do not breathe in vapor and spray mist. May cause Irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness. Avoid contact with eyes and skin. In case of contact with eye rinse immediately with plenty of water and seek medical advice. If swallowed, rinse mouth with plenty of water (only if the person is conscious) show this container or label to a medical practitioner. Its vapor may cause drowsiness and dizziness. In case of fire use foam, dry powder, CO<sub>2</sub> fire extinguisher. Never use water. Take precautionary measure against static charges. Use only in well ventilated place. Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Dispose off paint waste in accordance with the appropriate environment quality regulation.