

Brighto All Wood Sealer

Brighto All Wood Sealer Is a fast drying nitrocellulose based clear sealer for wooden surfaces. It protects top coat by sealing the pours base without hiding the wood grains. It is used on soft wood, hard wood, plywood, furniture, timberwork such as doors, windows, tables, cupboards etc.

PACK SIZE: 0.91 L 3.64 L

COLOR RANGE: Clear

DRYING TIME:

Depends on temperature, humidity, air movements and film thickness

Touch Dry 15 - 20 Minutes

Recoat 1– 1 1/2 Hours

APPLICATION: Spray

THINNING:

Conventional spray: 100 - 150% with BRIGHTO NC THINNER

CLEANING UP:

Clean all equipment with BRIGHTO NC THINNER immediately after use.

THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 11 – 13 m² /litre /coat.

SURFACE PREPARATION:

Before application, the surface should be clean, dry and free from oil, grease, dust, wax etc. Rub down the surfaces with the help of abrasive paper surface must be scuffed in the direction of grains. Clean with the help of clean cloth. Apply 1-2 coats of Brighto All Wood Sealer. Allow it to dry. Slightly rub down

the surface with the help of abrasive paper after each coat. Clean with the help of clean cloth. Apply 2-3 coats of Brighto All Wood Lacquer Gloss/Matt as top coat. Stir the product thoroughly before use.

FLASH POINT: 20°C

COMPOSITION (nominal):

Pigment: Inert filler

Binder: Nitrocellulose, SO Alkyd

Solvent: Volatile solvents BA,IPA ,XYLENE

VOLUME SOLIDS: 32 ± 2% (nominal)

FILM THICKNESS/COAT

Wet: 50 - 75 Micrometers

Dry : 17 – 25 Micrometers

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION

Highly inflammable. Keep container tightly closed, up right and out of reach of children. Keep away from the source of ignition e.g cigarette, matchbox, lighter etc. Protect from extremes of temperatures and store in a cool and dry place. Keep away from food, drink and animal feeding stuff. Keep container tightly closed. Wear suitable gloves, mask and safety goggles during application. Do not breathe in vapor and spray mist. May cause Irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, rinse mouth with plenty of water (only if the person is unconscious) show this container or label to a medical practitioner. Its vapor may cause drowsiness and dizziness. In case of fire use foam, dry powder, CO2 fire extinguisher. Never use water. Take precautionary measure against static charges. Use only in well ventilated place. Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Dispose of any paint waste in accordance with the appropriate environmental quality regulation.