

Brighto Aluminium Finish

Brighto Aluminium Finish is a silver paint with a high metallic luster which protects the surface from corrosion, discolorations and effects of mild heat. Typical use includes chimneys, pipelines, storage vessels, stream pipes, light poles, bridges, door and heat exchangers.

PACK SIZE: 0.25L 0.91L 3.64L

COLOR RANGE: Silver

DRYING TIME:

Depends on temperature, humidity, air movements and film thickness

Touch Dry: 1-2Hours

Recoat: 3-4Hours

THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 14-16m²/litre/coat.

APPLICATION: Brush Roller Spray

CLEANING UP:

Clean all equipment with mineral turpentine immediately after use.

SPRAY RECOMMENDATIONS:

Conventional spray satisfactory through most equipment.

SURFACE PREPARATION:

New, bare, old or previously painted surfaces must be clean, dry and free from wax, dust, rust and all unwanted material. Clean the surface by rubbing down with abrasive paper. Brush down previously painted surfaces and dust it off. Apply Brighto Red Oxide Prime on all metal surfaces in order to prevent from rust. Allow the surface to dry completely. Stir paint thoroughly before use.

SYSTEM INFORMATION: Metal

COMPOSITION (nominal):

Pigment: Aluminum Paste

Solvent: Mineral Turpentine

VOLUME SOLIDS:

White 31 + 2% (nominal)

FILM THICKNESS/COAT:

Wet: 50-75 Micrometers Dry: 15-23 Micrometers

THINNING: Ready to use