

Brighto Exterior Filler

Brighto Exterior Filler is a 100% acrylic-based, ready-to-use filler that has an excellent whiteness, coverage and applications properties. It's high quality filling properties has made it ideal for use on all types of exterior masonry surfaces. It provides a smooth base for the application of All Weather. Brighto Exterior Filler is for exterior use.

PACK SIZE: 6 Kg 20 Kg

COLOR RANGE: White only

FILM PROPERTIES:

Water Resistance: Will tolerate the levels of atmospheric humidity present in normal environments.

COMPOSITION (nominal):

Pigment: Inert filler

Binder: Acrylic Copolymer Emulsion

Solvent: Water

VOLUME SOLIDS:

49 ± 2% (nominal)

FILM THICKNESS/COAT:

Wet: 100-150 Micrometers Dry: 49-73 Micrometers

DRYING TIME:

Depends on temperature, humidity, air movements and film thickness

Touch Dry: 2-3 Hours

Recoat: 6-8 Hours

THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 6-10m²/litre/coat.

SURFACE PREPARATION:

New, bare, old or previously painted surfaces must be clean, dry and free from dust or wax. Clean the surface by rubbing down with the abrasive paper. Brush down previously painted surfaces completely and make the surface smooth. For large holes and cracks use plaster of Paris or white cement. Allow it to dry. Apply Brighto Exterior Primer in order to seal the surface from water and salts. Allow surface to dry completely. Then apply Brighto Exterior Filler.

APPLICATION: Putty applicator

THINNING:

Ready to use: No thinning required

Conventional Spray: Not applicable

SPRAY RECOMMENDATIONS:

Not applicable

Conventional Spray

CLEANING UP:

Clean all equipment with clean water immediately after use.

SYSTEM INFORMATION:

New, old or previously painted surfaces.