

## Brighto Exterior Primer

Brighto Exterior Primer is a water-based primer for all types of exterior masonry surface, both new and previously decorated such as brickwork, plaster and cement. It reduces damage from alkali, salts and seals the surfaces.

**PACK SIZE:** 4L 16L

**COLOR RANGE:** White only

### FILM PROPERTIES:

Water Resistance: Will tolerate the levels of atmospheric humidity present normal environments.

### COMPOSITION (nominal):

Pigment: Lightfast Pigments

Binder: Acrylic Copolymer

Solvent: Water

### VOLUME SOLIDS:

37 ± 2% (nominal)

### FILM THICKNESS/COAT:

Wet: 50-75 Micrometers Dry: 18-27 Micrometers

### DRYING TIME:

Depends on temperature, humidity, air movements and film thickness

Touch dry: 2-3 Hours

Recoat: 6-8 Hours

### THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 13-20m<sup>2</sup>/litre/coat.

**APPLICATION:** Brush Roller Spray

**THINNING:**

Brush or Roller: 10-25%

Conventional spray: 30-40%

**SPRAY RECOMMENDATIONS:**

Conventional spray satisfactory through most equipment.

**CLEANING UP:**

Clean all equipment with water immediately after use.

**SURFACE PREPARATION:**

New, bare, old or previously painted surface must be clean dry, free from wax and dust. Clean the surface by rubbing down with abrasive paper. Brush down previously painted surfaces completely and make the surface smooth. Dust it off with the help of cloth. Stir the paint thoroughly before use.

**SYSTEM INFORMATION:**

Powdery surfaces

Masonry

Normal, sound surfaces (previously painted