

## Brighto Gray Oil Putty

Brighto Gray Oil Putty is excellent quality putty which has been developed for gap filling in automobile surface and provides tough and completely smooth surface. It is suitable for use on buses, trucks and each type of automobiles.

**PACK SIZE:** 0.91L

**COLOR RANGE:** Gray

### **DRYING TIME:**

Depends on temperature humidity, air movements and film thickness

Touch Dry: 2-4 Hours

Recoat: 6-8 Hours

### **THEORETICAL COVERAGE:**

A guide to the theoretical coverage which can be achieved under normal conditions is 6-10m<sup>2</sup>/litre/coat.

**APPLICATION:** Scrapers

### **CLEANING UP:**

Clean all equipment with mineral turpentine immediately after use.

### **SURFACE PREPARATION**

New or old surface must be dry and free from wax, dust, brush down previously painted surface completely. Clean the surface by rubbing down with the help of abrasive paper. Stir thoroughly before use.

**THINNING:** Scrapers

**SYSTEM INFORMATION:** Buses Trucks Cars Iron

**FILM PROPERTIES:**

Chemical Resistance: Resistant to mild chemical fume attack.

**COMPOSITION (nominal):**

Pigment: Inert Filler  
Binder: Alkyd  
Solvent: Mineral Turpentine

**VOLUME SOLIDS:**

64 ± 2% (nominal)

**FILM THICKNESS/COAT:**

Wet: 100-150 Micrometers      Dry: 64-96 Micrometers

**FLASH POINT:** 100°C