

Brighto Interior Filler

Brighto Interior Filler is a low VOC and Breathable high quality filler suitable for all types of interior masonry surfaces such as brick work, chipboard, hard board, plaster and cement etc. It gives more whiteness and coverage with excellent filling properties. It provides smooth finish for top coats.

PACK SIZE: 5 Kg 20 Kg

COLOR RANGE: White only

FILM PROPERTIES

Water Resistance: Will tolerate the levels of atmospheric humidity present in normal environment.

COMPOSITION (nominal):

Pigment: Inert filler
Binder: Acrylic Copolymer Emulsion.
Solvent: Water

VOLUME SOLIDS: 46 ± 2% (nominal)

FILM THICKNESS/COAT

Wet : 100 - 125 Micrometers

Dry : 46 – 57.5 Micrometers

DRYING TIME:

Depends on temperature, humidity, air movements and film thickness

Touch dry: 2 - 4 Hours

Recoat: 4 - 6 Hours

THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 8 - 10 m²/litre/coat.

APPLICATION: Putty applicator

THINNING: Ready to use

Conventional spray: Not applicable

CLEANING UP:

Clean all equipment with clean water immediately after use.

SURFACE PREPARATION:

New, bare, old or previously painted surfaces must be clean, dry and free from dust or wax. Clean the surface by rubbing down with abrasive paper. Brush down previously painted surface completely and make the surface smooth. For large holes and cracks, use plaster of Paris or white cement. Allow it to dry. Apply Brighto Interior Primer in order to seal the surface from water and salts. Allow surface to dry completely. Then apply Brighto Interior Filler.

FLASH POINT: 34°C

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION:

Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contact with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO2 fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose of paint waste in accordance with appropriate environmental quality requirements. Any advice, recommendations, information, assistance or service provided by Brighto Paints Pvt. Ltd. in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.