

## Brighto Interior Primer

Brighto Interior Primer is a water based wall sealer which protects against alkali and moisture. It is breathable primer which allows water vapors to evaporate. It is a top quality primer for use on masonry surfaces including concrete, brick work, plaster, cement and wall boards etc.

**PACK SIZE:** 4L 16L

**COLOR RANGE:** White only

### FILM PROPERTIES

Water Resistance: Will tolerate the levels of atmospheric humidity present in normal environments.

### COMPOSITION (nominal):

Pigment: Lightfast Pigments

Binder: Acrylic copolymer

Solvent: Water

**VOLUME SOLIDS:** 40 ± 2% (nominal)

### FILM THICKNESS/COAT

Wet: 75- 100 Micrometers

Dry : 30 - 40 Micrometers

### DRYING TIME:

Depends on temperature, humidity, air movements and film thickness

Touch dry: 2 - 4 Hours

Recoat: 4 - 6 Hours

### THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 10 - 13m<sup>2</sup>/liter /coat.

**APPLICATION:** Brush   Roller   Spray

**THINNING:**

Brush or Roller: 10 - 25%

Conventional spray:    30 - 40%

**CLEANING UP:**

Clean all equipment with water immediately after use.

**SURFACE PREPARATION:**

New, bare, old or previously painted surface must be clean dry, free from wax and dust. Clean the surface by rubbing down with abrasive paper. Brush down previously painted surfaces completely and make the surface smooth. Dust it off with the help of cloth. Stir thoroughly before use.

**FLASH POINT:** 33°C

**SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION:**

Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contact with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO2 fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose of paint waste in accordance with appropriate environmental quality requirements.

Any advice, recommendations, information, assistance or service provided by Brighto Paints Pvt. Ltd. in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.