

Brighto Plastic Emulsion

Brighto Plastic Emulsion is top quality Emulsion paint ideal for interior walls, ceiling, old and new cements concrete plaster, chipboard and hardboard. Brighto Plastic Emulsion is a tough and long-lasting paint with completely flat finish, which helps to hide imperfections of surface; Brighto Plastic Emulsion dries out to a smooth finish without brush marks.

USAGE:

Brighto Plastic Emulsion is used for all normal interior masonry surfaces including brickwork, Plaster, cement and wallboards.

PACK SIZE: 1L 4L 16L

COLOR RANGE: See appropriate shade card

DRYING TIME:

Depends on temperature, humidity, air movements and film thickness

Touch dry: 2-3 Hours

Recoat: 6-8 Hours

THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 10-13.5m²/litre/coat.

APPLICATION: Brush Roller Spray

THINNING:

Brush or Roller: 10-25%

Conventional spray: 30-40% depending upon application methodology

CLEANING UP:

Clean all equipment with clean water immediately after use.

SURFACE PREPARATION:

New, bare, old or previously painted surfaces must be clean, dry and free from dust or wax. Clean the surface by rubbing down with abrasive paper. Brush down previously painted surface completely and make the surface smooth. For large holes and cracks use plaster of Paris or white cement. Allow it to dry. Apply Brighto Interior Primer in order to seal the surface from water and salts. Allow surface to dry completely. Then apply Brighto Super Filler. After drying, apply Brighto Plastic Emulsion.

- . Brighto Interior Primer
- . Brighto Super Filler
- . Brighto Plastic Emulsion

FILM PROPERTIES:

Water Resistance: Will tolerate the levels of atmospheric humidity present in normal environments

VOLUME SOLIDS: White 38 - 2 % (nominal), other colors will vary.

FILM THICKNESS/COAT:

Wet: 50-75 Micrometers Dry: 28-38 Micrometer