

Brighto Red Oxide Primer

Brighto Red Oxide Primer is an excellent quality primer which protects the iron and steel from rust. It is specially formulated with the help of non-rusting raw material. It is a best protective paint.

USAGE:

Brighto Red Oxide Primer is used for interior and exterior metal work including steel work and iron.

PACK SIZE: 0.91L 3.64L 14.56L

COLOR RANGE: Red only

DRYING TIME:

Depends on temperature, humidity, air movements and film thickness

Touch Dry: 2-4 Hours

Recoat: 6-8 Hours

THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 13-20m²/litre/coat.

APPLICATION: Brush Roller Spray

SPRAY RECOMMENDATIONS:

Conventional spray satisfactory through most equipment.

CLEANING UP:

Clean all equipment with mineral turpentine immediately after use.

SURFACE PREPARATION:

New or previously painted surfaces must be clean, dry and free from grease, rust, dust etc. Rub down the surface with the help of abrasive paper and remove previous paint. Clean with the help of cloth. Stir the paint thoroughly before use.

SYSTEM INFORMATION: Metal

FLASH POINT: 33°C

THINNING:

Brush or Roller: 10-25% Conventional spray: 30-40%

COMPOSITION (nominal):

Pigment: Red Oxide

Binder: Alkyd

Solvent: Mineral Turpentine

VOLUME SOLIDS:

48 ± 2% (nominal)

FILM THICKNESS/COAT:

Wet: 50-75 Micrometers Dry: 24-36 Micrometers