

Brighto Sterling Gold

Brighto Sterling Gold is a premium quality water based wall paint, based on 100% acrylic. It is intended for internal and external applications which gives a unique sparkling luxurious decorative finishes.

PACK SIZE: 1L 4 L

COLOR RANGE: See Brighto Sterling Gold shade card

FILM PROPERTIES

Water Resistance: Will tolerate the levels of atmospheric humidity present in normal environments.

COMPOSITION (nominal):

Pigment: Lightfast Pigments

Binder: Acrylic Copolymer Emulsion

Solvent: Water

VOLUME SOLIDS: $29 \pm 2\%$ (nominal), other colors will vary

FILM THICKNESS/COAT

Wet: 100 - 125 Micrometers

Dry: 29 - 36 Micrometers

DRYING TIME:

Depends on temperature, humidity, air movements and film thickness

Touch Dry: 2 - 4 Hours

Recoat: 4 - 6 Hours

THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 8 – 10 m² /liter /coat.

APPLICATION: Brush Roller Spray Sponge

THINNING:

Brush or Roller: Ready to use, 10% (if required)

CLEANING UP:

Clean all equipment with clean water immediately after use.

SURFACE PREPARATION:

New, bare, old or previously painted surfaces must be clean, dry and free from dust or wax etc. Clean the surface by rubbing down with abrasive paper. Brush down previously painted surface completely and make the surface smooth. For large holes and cracks use plaster of Paris or white cement. Allow it to dry. For interior application, apply Brighto Interior Primer in order to seal the surface from water and salts. Allow surface to dry completely then apply Brighto Super Filler and allow it to dry. For exterior application , apply Brighto Exterior Primer in order to seal the surface from water and salts. Allow surface to dry completely then apply Brighto Exterior Filler and allow it to dry. Rub down the surface with abrasive paper and dust it off. Now the surface will be smooth and ready for Brighto Sterling Gold to be applied. Stir the paint thoroughly before use.

FLASH POINT: 31°C

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION:

Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contacts with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO2 fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose of paint

waste in accordance with appropriate environmental quality requirements. Any advice, recommendations, information, assistance or service provided by Brighto Paints Pvt. Ltd. in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.