

## Brighto Super Emulsion

Brighto Super Emulsion is superior quality paint. It is specially formulated. It has excellent application properties and a smooth pleasing finish. It can be applied on interior walls, ceiling, old new concrete plaster, chipboard and hardboard.

### USAGE:

Brighto Super Emulsion is used for all normal interior masonry surfaces including brickwork, plaster, cement and wallboards.

**PACK SIZE:**     0.91L            3.64L            14.56L

**COLOR RANGE:**     See appropriate shade card

### DRYING TIME:

Depends on temperature, humidity, air movements and film thickness

Touch Dry:     2-3 Hours

Recoat:        4-6 Hours

**APPLICATION:**     Brush            Roller            Spray

### CLEANING UP:

Clean all equipment with water immediately after use.

### THINNING:

Brush or Roller:            10-25%

Conventional Spray: 30-40%

**SURFACE PREPARATION:**

New, bare, old or previously painted surfaces must be clean, dry and free from dust or wax. Clean the surface by rubbing down with abrasive paper. Brush down previously painted surfaces completely and make the surface smooth. For large holes and cracks use plaster of Paris or white cement. Allow it to dry. Apply Brighto Interior Primer in order to seal the surface from water and salts. Allow surface to dry completely. Then apply Brighto Filler and allow it to dry. Rub down the surface with abrasive paper and dust it off. Now the surface will be smooth and ready for Brighto Super Emulsion to be applied. Stir the paint thoroughly before use.

. Brighto Interior Primer

. Brighto Super Filler

. Brighto Super Emulsion

**THEORETICAL COVERAGE:**

A guide to the theoretical coverage which can be achieved under normal conditions is 10-14m<sup>2</sup>/litre/coat.

**SPRAY RECOMMENDATIONS:**

Conventional spray satisfactory through most equipment.

**FILM PROPERTIES:**

Water Resistance: Will tolerate the levels of atmospheric humidity present in normal environments.

**COMPOSITION (nominal):**

Pigment: Lightfast Pigments

Binder: PVA Copolymer Emulsion

Solvent: Water

**VOLUME SOLIDS:**

White 45 + 2% (nominal), other colors will vary.

**FILM THICKNESS/COAT:**

Wet: 75-100 Micrometers      Dry: 33-45 Micrometers