

Brighto Super Sealer

Brighto Super Sealer used to protect and seal masonry plaster and concrete surfaces. It reduces damages produced by alkali and salts. It also gives better coverage to topcoat.

USAGE:

Brighto Super Sealer is used for interior masonry surface both new and previously painted surfaces such as brickwork, plaster and cement. It reduces damage from alkali and salts and seals powdery, porous surfaces.

PACK SIZE: 1L 4L 16L

COLOR RANGE: White only

DRYING TIME:

Depends on temperature humidity, air movements and film thickness

Touch Dry: 2-4 Hours

Recoat: 6-8 Hours

THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 10-13m²/litre/coat.

APPLICATION: Brush Roller Spray

CLEANING UP:

Clean all equipment with mineral turpentine immediately after use.

SURFACE PREPERATION:

New, bare, old or previously painted surface must be clean, dry, free from wax and dust. Clean the surface by rubbing down with abrasive papaer. Brush down previously painted surfaces completely and make the surface smooth. Dust it off with the help of cloth. Stir the paint thoroughly before use.

SYSTEM INFORMATION:

Powdery surfaces

Masonry

Normal, sound surfaces (previously painted)

THINNING:

Brush or Roller: 10-25% Conventional spray: 30-40%

RECOMMENDATIONS:

Conventional spray satisfactory through most equipment.

FILM PROPERTIES:

Water Resistance: Not suitable where the surface is saturated.

COMPOSITION (nominal):

Pigment: Lightfast Pigments

Binder: Alkyd

Solvent: Mineral Turpentine

VOLUME SOLIDS: $46 \pm 2\%$ (nominal)

FILM THICKNESS/COAT:

Wet: 75-100 Micrometers Dry: 34-46 Micrometers