

Brighto Synthetic Clear Varnish

Brighto Synthetic Clear Varnish has a high gloss finish and has excellent abrasion resistance. Brighto Synthetic Clear Varnish is a solvent-based varnish suitable for use on all type of new or previously treated wood and metal. Typical use includes panelling, cane or wood furniture, windows, door and partitions.

PACK SIZE: 0.25L 0.75L 3L 12L

COLOR RANGE: Clear

COMPOSITION (nominal):

Pigment: N/A

Binder: Alkyd

Solvent: Mineral Turpentine

VOLUME SOLIDS: 34 ± 2% (nominal)

FILM THICKNESS/COAT

Wet: 50 - 75 Micrometers

Dry : 17 - 25 Micrometers

DRYING TIME:

Depends on temperature, humidity, air movements and film thickness

Touch Dry: 2-4 Hours

Recoat: 6-8 Hours

APPLICATION: Brush Roller Spray

SURFACE INFORMATION:

Surface generally must be clean, dry, free from all defective or poorly adhering material, dirt, grease and wax etc.

THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 14-20m² /litre/coat..

THINNING

Brush or Roller: 10-20%

Conventional spray: 30-40%

SPRAY RECOMMENDATIONS:

Conventional spray satisfactory through most equipment

CLEANING UP:

Clean all equipment with mineral turpentine immediately after use.

FLASH POINT: 33°C