

Brighto Synthetic Undercoat

Brighto Synthetic Undercoat is an excellent quality alkyl-based, non-absorbent, intermediate coat. It gives maximum enamel hold-out and provides smooth tough surface. It is highly recommended for use on all interior and exterior surfaces like wood, metal iron, cement etc. It is overcoated with Brighto Finishes.

USAGE:

Brighto Synthetic Undercoat is used on all interior and exterior surfaces like wood, metal and iron etc.

PACK SIZE: 0.91L 3.64L

COLOR RANGE: White only

DRYING TIME:

Depends on temperature, humidity, air movements and film thickness

Touch Dry: 2-4 Hours

Recoat: 6-8 Hours

THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 13.5-20m²/litre/coat.

APPLICATION: Brush Roller Spray

RECOMMENDATIONS:

Conventional spray is satisfactory through most equipment.

CLEANING UP:

Clean all equipment with mineral turpentine immediately after use.

SURFACE PREPARATION:

New, bare, old or previously painted surfaces must be clean dry, free from wax and dust. Clean the surface by rubbing down with abrasive paper. Brush down previously painted surfaces and dust it off.

SYSTEM INFORMATION: Wood Metal

FILM PROPERTIES:

Water Resistance: Resistant to the levels of atmospheric humidity present in normal, not suitable for use on immersed surface.

FLASH POINT: 31.5 °C

COMPOSITION (nominal):

Pigment: Lightfast Pigments

Binder: Alkyd

Solvent: Mineral turpentine

VOLUME SOLIDS:

50 + 2% (nominal)

FILM THICKNESS/COAT :

Wet: 50-75 Micrometers

Dry: 25-37 Micrometers

THINNING:

Brush or Roller: 10-25%

Conventional spray: 30-40%