

Brighto Wall Emulsion

Brighto Wall Emulsion is top quality emulsion paint. It is ideal for walls, ceiling, old and new cements, concrete, plaster, chipboard and hardboard. Brighto Wall Emulsion is a tough and long-lasting paint with completely flat finish, which helps to hide imperfections of surface. Brighto Wall Emulsion dries out to a smooth flat finish without brush marks. It can be used on both interior and exterior surfaces.

USAGE:

Brighto Wall Emulsion is used in interior masonry surfaces including brickwork, plaster, cement and wallboards.

PACK SIZE: 3.64L 14.56L

COLOR RANGE: See appropriate shade card

THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 10-14m²/litre/coat.

APPLICATION: Brush Roller Spray

SPRAY RECOMMENDATIONS:

Conventional spray satisfactory through most equipment.

CLEANING UP:

Clean all equipment with water immediately after use.

SURFACE PREPARATION:

New, bare, old or previously painted surfaces must be clean, dry and free from dust or wax. Clean the surface by rubbing down abrasive paper. Brush down previously painted surfaces completely and make the surface smooth. For large holes and cracks, use plaster of Paris or white cement. Allow it to dry. Apply Brighto Interior Primer in order to seal the surface from water and salts. Allow surface to dry completely. Then apply Brighto Wall Putty and allow it to dry. Rub down the surface with abrasive paper

and dust it off. Now the surface will be smooth and ready for Brighto Wall Emulsion to be applied. Stir the paint thoroughly before use.

- . Brighto Interior Primer
- . Brighto Super Filler
- . Brighto Super Emulsion

THINNING:

Brush or Roller: 10-25%

Conventional spray: 30-40% depending upon application methodology

DRYING TIME:

Depends on temperature, humidity, air movements and film thickness

Touch Dry: 2-3 Hours

Recoat: 4-6 Hours

FILM PROPERTIES:

Water Resistance: Will tolerate the levels of atmospheric humidity present in normal environments.

COMPOSITION (nominal):

Pigment: Lightfast Pigments

Binder: PVA Copolymer Emulsion

Solvent: Water

VOLUME SOLIDS:

White 42 ± 2 % (nominal), other colors will vary

FILM THICKNESS/COAT:

Wet: 75-100 Micrometers

Dry: 31-42 Micrometers