

Brighto Wall Putty

Brighto Wall Putty is a good quality water-based filler. It smoothens the surface for application of Brighto Topcoat. It has good filling and sanding properties.

USAGE:

Brighto Wall Putty is used on all types of interior masonry surfaces. It provides a smooth base for the application of all decorative products.

PACK SIZE: 5kg 20kg

COLOR RANGE: White only

DRYING TIME:

Depends on temperature humidity, air movements and film thickness

Touch Dry: 2-4 Hours

Hours Recoat: 4-6 Hours

APPLICATION: Putty applicator

CLEANING UP:

Clean all equipment with clean water immediately after use.

SURFACE PREPARATION:

New, bare old or previously painted surfaces must be clean, dry and free from dust or wax. Clean the surface by rubbing down with abrasive paper. Brush down previously painted surface completely and make the surface smooth. For large holes and cracks use plaster of Paris or white cement. Allow it to dry. Apply Brighto interior Primer in order to seal the surface from water and salts. Allow surface to dry completely. Then apply Brighto Wall Putty.

SYSTEM INFORMATION:

New, old or previously painted surfaces.

FILM PROPERTIES:

Water Resistance: Will tolerate the levels of atmospheric humidity present in normal environment.

COMPOSITION (nominal):

Pigment: Inert Filler
Binder: Acrylic Copolymer Emulsion
Solvent: Water

VOLUME SOLIDS:

49 + 2% (nominal)

FILM THICKNESS/COAT:

Wet: 100-150 Micrometers Dry: 49-73 Micrometers

THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 6-10m²/litre/coat.

THINNING: Ready to use