

Brighto Synthetic Metallic Enamel

Brighto Synthetic Metallic Enamel is an excellent quality paint suitable for use on all types of interior and exterior wood and metal surfaces. It gives sparkling and lustrous finish. It gives complete protection against water, rust and dust etc.

USAGE:

Brighto Metallic Enamel is used on all types of interior and exterior wood and metal surfaces.

PACK SIZE: 0.25L 0.91L 3.64L

COLOR RANGE: See appropriate shade card

DRYING TIME:

Depends on temperature humidity, air movements and film thickness

Touch Dry: 2-4 Hours

Recoat: 6-8 Hours

THEORETICAL COVERAGE:

A guide to the theoretical coverage which can be achieved under normal conditions is 13.5-20m²/litre/coat.

APPLICATION: Spray

CLEANING UP:

Clean all equipment with mineral turpentine/super petrol immediately after use.

SURFACE PREPARATION:

New, bare, old or previously painted surfaces must be clean, dry and free from wax, dust, rust and all unwanted material. Clean the surface by rubbing down with abrasive paper. Brush down previously painted surfaces and dust it off. Apply Brighto Red Oxide Primer on all metal surfaces in order to prevent from rust. Apply Brighto Undercoat on all wooden surfaces. Apply Brighto Gray Oil Putty on all automobile surfaces. Allow the surface to dry completely. Stir paint thoroughly before use.

SYSTEM INFORMATION: Wood Metal Automobile

THINNING: Conventional spray 20-25 %

COMPOSITION (nominal):

Pigment: Lightfast Pigments

Binder: Alkyd Resin

Solvent: Mineral Turpentin / Super Petrol

VOLUME SOLIDS: Silver $50 \pm 2\%$ (nominal), other colors will vary

FILM THICKNESS/COAT:

Wet: 60-75 Micrometers Dry: 25-35 Micrometers

FLASH POINT: 38°C